



Storinator
SERIOUS STORAGE

Technical Specifications for the Storinator **Q30** Enhanced Configuration

| | |
|----------------------------------|--|
| Case | 4U Custom Case (Front plate with rack ears standard) |
| Power Supply | 750W Corsair Power Supply |
| HBA Cards | 1 Rocket 750 Host Bus Adaptor Card OR 2 LSI9201 16I Host Bus Adaptor Cards (SATA, SAS & SSD) |
| Processor | 1 Intel Hex Core E5-2620 processor |
| Motherboard | 1 SuperMicro MBD-X10SRL-F-O (ATX) (6 free for expansion PCIe slots for Rocket 750 HBA cards and 5 free expansion PCIe slots for LSI HBA cards and) |
| NIC Ports | 2 x 1GbE NIC ports standard (Upgradable to 10GbE Fibre or Copper NICs) |
| RAM | 16GB DDR4 RAM - 2 KVR1611S4/8 KNG 16G DDR4 1600 ECC |
| Boot Drive | 1 120GB SSD Redundant Boot Drive OR 2 SDSSDHII-120GB-G25-Sandisk Ultra II 120GB SSD-Internal- Read 550MB/s - Write 500MB/s |
| Case Fan | 6 Noctura NF-P12-1300 120mm Case Fans |
| Direct-Wired Cables | 9 SFF 8087 to 4 8482 Cables |
| On/Off Switch | 1 FrozenCPU ele-302 Bulgin Vandal Momentary LED 12" Power Switch 2-Pin Prewired Vandal Momentary Power Switch , 1' Sleeved |
| Sliding Rails | 2 SuperMicro Ball Bearing Sliding Rails (MCP-290-00530-0N) |
| Fan Anti Vibration Mounts | 24 AP-1003W-B Black Anti-Vibration Silicone Washers |