

VISIT: www.45drives.com PHONE: 1-866-594-7199 EMAIL: info@45drives.com



Technical Specifications for the Storinator S45 Enhanced Configuration

Case 4U Custom Case (Front plate with rack ears standard)

Power Supply Redundant option:

1 950W 2+1 Redundant Zippy M3W-P6950L Power Supply

Non-Redundant option:

1 850W ATX Standard PSL-6850P Power Supply

HBA Cards 2 Rocket 750 Host Bus Adaptor Cards OR

3 LSI9201 16I Host Bus Adaptor Cards (SATA, SAS & SSD)

Processor 1 Intel Hex Core E5-2620 processor

Motherboard 1 SuperMicro MBD-X10SRL-F-O (ATX)

(5 free for expansion PCIe slots for Rocket 750 HBA cards and 4 free expansion PCIe

slots for LSI HBA cards and)

NIC Ports 2 x 1GbE NIC ports included & 10GbE NIC included

Choice of: • AOC-STGN-i2s 2PT, two port Fibre SFP+ (transceivers not included)

• X540T2BLK, two port RJ45 Copper

RAM 16GB DDR4 RAM - 2 KVR1611S4/8 KNG 8G DDR4 1600 ECC

Redundant Boot Drives 120GB SSD Redundant Boot Drives- 2 SDSSDHII-120GB-G25-

Sandisk Ultra II 120GB SSD-Internal-Read 550MB/s-Write 500MB

Case Fan Redundant Supply:

5 DF1212025BH-3G Dynatron 120x120x25mm 2600RPM Cooling fan

Non-Redundant Supply:

6 DF1212025BH-3G Dynatron 120x120x25mm 2600RPM Cooling fan

Direct-Wired Cables 12 SFF 8087 to 4 SFF 8482 cables

On/Off Switch 1 FrozenCPU ele-302 Bulgin Vandal Momentary LED 12"

Power Switch

2-Pin Prewired Vandal Momentary Power Switch, 1'Sleeved

Sliding Rails 2 SuperMicro Ball Bearing Sliding Rails (MCP-290-00530-0N)

Fan Anti Vibration Mounts 24 AP-1003W-B Black Anti-Vibration Silicone Washers