



Storinator
SERIOUS STORAGE

Technical Specifications for the Storinator **XL60** Base Configuration

Case	4U Custom Case (Front plate with rack ears standard)
Power Supply	1 950W 2+1 Redundant Zippy M3W-P6950L Power Supply
HBA Cards	2 Rocket 750 Host Bus Adaptor Card
Processor	1 Intel Dual Core i3-3240 processor
Motherboard	1 SuperMicro MBD-X9SCM-F (Micro ATX) (2 PCI slots free with Rocket 750 HBA cards)
NIC Ports Choice of:	2 x 1GbE NIC ports included & 10GbE NIC included • AOC-STGN-i2s 2PT, two port Fibre SFP+ (transceivers not included) • X540T2BLK, two port RJ45 Copper
RAM	8GB DDR3 RAM - 2 KVR1611S4/8 KNG 4GB DDR3 1600 ECC
Redundant Boot Drives	120GB SSD Redundant Boot Drives -2 SDSSDHII -120G-G25- Sandisk Ultra II 120GB SSD-Internal-Read 550MB/s-Write 500MB
Case Fan	5 DF1212025BH-3G Dynatron 120x120x25mm 2600RPM Cooling Fan
Direct-Wired Cables	16 SFF 8087 to 4 SFF 8482 Cables
On/Off Switch	1 FrozenCPU ele-302 Bulgin Vandal Momentary LED 12" Power Switch 2-Pin Prewired Vandal Momentary Power Switch , 1' Sleeved
Sliding Rails	2 SuperMicro Ball Bearing Sliding Rails (MCP-290-00530-0N)
Fan Anti Vibration Mounts	24 AP-1003W-B Black Anti-Vibration Silicone Washers