



# Technical Specifications

## XL60

### Base Configuration

|                                  |  |
|----------------------------------|--|
| Case                             | 4U Custom Case (Front plate with rack ears optional)   |
| Power Supply                     | 1 1400W 2N Redundant, High-Efficiency Zippy MTW2-5AD0B2V PSU with PMBus Remote Monitoring  |
| HBA Card                         | 4 LSI 9305 HBA (Recommended)<br>Other options available see configurator   |
| Processor                        | 1 Intel Xeon E3-1220 V5  |
| Motherboard                      | X11SSM-F   |
| NIC Ports                        | 2 x 1GbE NIC ports included & 10GbE NIC included<br>• AOC-STGN-i2s 2PT, two port Fibre SFP+ (transceivers not included)<br>• X540T2BLK, two port RJ45 Copper |
| RAM                              | 8GB DDR4 2133MHz (Expandable to 64GB)  |
| Boot Drive                       | HP S700 PRO 128GB SSD - Internal (Single or Redundant )  |
| Case Fan                         | 5 DF1212025BH-3G Dynatron 120x120x25mm 2600RPM Cooling Fan   |
| Direct-Wired Cables              | 16 SFF 8087 to 4 SFF 8482 Cables (6Gbe)<br>16 SFF 8643 to 4 SFF 8482 Cables (12Gbe)  |
| Cable Management Arm<br>Optional | SuperMicro MCP-290-00073-0N<br>*Note: you will need to use the included attachment SC829   |
| Sliding Rails<br>Optional        | 2 SuperMicro Ball Bearing Sliding Rails (MCP-290-00530-0N)   |
| LCD Screen<br>Optional           | HighPoint HPT-LCD-02 LCD screen<br>*Note: only available with Rocket 750 Host Bus Cards  |
| On/Off Switch                    | 1 FrozenCPU ele-302 Bulgin Vandal Momentary LED  |

Technical specifications for the Storinator line of products is subject to change at any time. Please refer to [www.45drives.com](http://www.45drives.com) for the most up-to-date specifications.